

Invitation to Bid HNS 21-12

NOTE: Contractors are not authorized to visit the property before or after the bid walk, without being accompanied by the City's Rehabilitation Specialist.

Documents included in Package:

- 1) Instruction to Bidders
- 2) Specs by Location/Trade (Scope of Work)
- 3) Subcontractor Certifications (if applicable)
- 4) Floor Plan / Site Drawing (if applicable)

Bid Walk & Bid Opening:

Project Address: 422 Ridgeway Ave.	Rehab with Lead Hazards Control
Bid Walk: September 10, 2020 @ 10:00 a	am
Bid Opening: September 17, 2020 @ 2:0	0 pm
Client Name:	Contact Number:
Project Manager: Mike Taylor	Contact Number: 704-336-4115

Bid Walk and Bidding Instructions:

All bid walks are mandatory.

If you are going to be late the policy is the following:

Contact me BEFORE the start time if you are going to be late. If you are going to be more than 10 minutes late, we will proceed without you and you will not be permitted to bid.

The day of a bid walk the best way to reach me is at Mike Taylor (cell # 980-215-1156).

Bids must be received by the date, time and place specified. All others will be considered non responsive and disqualified.

The Bids will be opened at 600 East Trade St. immediately following the above due date and time.





Company Acknowledgement:

The undersigned, having become thoroughly familiar with the terms, conditions, limitations, and provisions of the housing improvement work to be performed at <u>422 Ridgeway Ave.</u> to be funded through the City of Charlotte Neighborhood & Business Services, in addition, having fully inspected the site in all particulars, hereby proposes and agrees to fully perform the work within the time stated and in strict accordance with the proposed contract documents including furnishing of any and all labor and materials, and to do all work required to complete said Work in accordance with the advised respective contractual, for the sum of money:

All labor, materials, services and equipment necessary for the completion of the Work shown on the Drawings and in the Specifications:

		<u>Dollars (Ş</u>
Written total		
Specs Dated: 8/19/2020	Number of Pages:	9 pages w/ bath layout and lead scope with
floor plan		
Addenda # 1 Dated:	Number of Pages:	
Addenda # 2 Dated:	Number of Pages:	
Project Schedule: Minimum Sto	art Date -	
Completion Deadline:		
Completion Deadine:		

Please Print and Sign:	
Company Name/Firm:	
Authorized Representative Name:	
Signature:	Date:



Requirements For Bidders

The City awards rehabilitation bids to the lowest responsive and responsible bidder. A responsible bidder for the safe home program is one who:

- 1) Is a licensed general contractor in the State of North Carolina;
- 2) Has an Renovate, Repair & Paint Certification (http://www2.epa.gov/lead/renovation-repair-and-painting-program);
- 3) Is not listed on a local, state or federal debarment list;
- 4) Carries an appropriate amounts of insurance;
- 5) Can provide references verifying the contractor has completed work of a similar scope in a good workmanship like manner or successfully completed prior work for the Safe Home program. Referenced work must have been completed in one year or less from date of this invitation to bid.

A responsive bidder must:

- 1) Submit all requested documentation on time;
- 2) Meet the above requirements for responsibility at the time of bid submittal;
- 3) Have the capacity to meet the required schedule for the project.
- 4) Existing rehab projects contracted by the contractor must be on schedule.

The City reserves the right to waive any minor informalities or irregularities, which do not go to the heart of the bid submittal or prejudice other offers, or to reject, for good and compelling reasons, any or all bid submittals.

Mikel Taylor Rehabilitation Specialist City of Charlotte Neighborhood and Business Services 600 E. Trade St. Charlotte, NC 29202

PH: (704) 336-4115 Fax: (704) 632-8575



Instructions to Bidders

Explanations to Bidders

Any explanation desired by a Contractor regarding the meaning or interpretation of the advertisement for bids, drawings, specifications, etc., must be requested in writing to the Rehabilitation Specialist with sufficient time allowed for a reply to each Contractor before the submission of their bids. Any interpretation made will be in the form of an addendum to the invitation for bids, drawings, specifications, etc., and will be furnished to all prospective Contractors. The Contractor must acknowledge any revision to the bid documents in the space provided on the bid form and it must be submitted with their bid package.

Preparation of Bids

Bids shall be submitted on the forms furnished, or copies thereof, and must be manually signed. If erasures or other changes appear on the forms, the person signing the bids must initial each erasure or change

- The Contractor's Bid Proposal must be properly executed and submitted on the form provided. Bids by Contractors must be received by the Rehabilitation Specialist at the time and place specified on the "Invitation to Bid"
- No bid will be considered unless all individual work items on the Bid Form including any addendums are priced. The sum of all work items must equal to the Total Bid Amount.
- Unless called for, alternate bids will not be considered
- Modification of bids already submitted will be considered if received at the office designated in the invitation for bids by the time set for opening of bids

Submittal of Bids

- Sealed bids will be submitted to the Safe Home Program Office as directed in the invitation to bid prior to or at the appointed bid opening time
- Bid will be time stamped on the date of delivery
- Each bid must be submitted in a sealed envelope bearing on the outside the name of the Contractor, the name of the project for which the bid is submitted, and the date and time of the bid opening
- All bids submitted must be typed or written in ink and signed by the Contractor's designated representative

G:\SELECTIVE REHAB TEAM\forms\bid forms and documents\Invitation to bid WARREN



SAFE HOME CITY OF CHARLOTTE NEIGHBORHOOD & BUSINESS SERVICES

- Failure to include all forms may result in rejection of a bid
- Required Bid Package Forms:
 - o Scope of Work
 - Addenda Acknowledgement
 - o Itemized Work Sheet
 - Subcontractor Certifications (if applicable)

NEIGHBORHOOD & BUSINESS SERVICES

http://housing.charlottenc.gov | 600 E. Trade Street | Charlotte, NC

Prepared By:

City of Charlotte Housing & Neighborhood Services 600 E. Trade Street Charlotte, NC 28202 (704) 336-7600

Property	Details
-----------------	----------------

Address: 422 Ridgeway Ave

Charlotte, NC 28204

Structure Type: Single Unit

Square Feet: 1310

Year Built: 1931

Property Value: 290100

Tax Parcel: 12704317

Census Tract:

Property Zone: Council District 1

Owner: Towanna Weathers Jones

Owner Phone: Home: (980) 613-8161

Program(s): Tested- HAS LEAD

LeadSafe 2016

Healthy Homes LBP 2016

Response Due: 8/19/2020 1:30 pm

SHFY2020

Repairs

<u>Description</u> <u>Floor</u> <u>Room</u> <u>Exterior</u>

All Contractor's Project Requirements

General Requirements

The contractor is responsible for all project requirements, including but not limited to:

All activities required by the City's COVID-19 Precautions for Residential Housing Rehabilitation Activities policy. Obtaining all permits required. Said permits shall include all items in this scope of work.

Provide temporary toilet facilities from job start until the completion of work.

Provide AS MANY roll-off dumpsters as needed without damaging the site. Collect construction debris using dust control methods. Remove dumpsters and repair any evidence of the dumpster use.

Contractor may haul debris away daily using dump trailers or trucks.

	Bid Cost:	x	<u> </u>		
		Base	Quantity	Total Cost	
Lead Based Paint Scope			General Re	quirements	
See attached scope. Work in the lead scope must be p	performed by a state certifi	ed lead abat	tement contractor.		
?	Bid Cost:	×	_		
		^ Base	Quantity	Total Cost	

Removal of Asbestos Containing Material

General Requirements

The third layer of flooring on the kitchen floor is an asbestos containing material (ACM). Also there is a small amount of insulation on some water supply lines that is presumed to be ACM.

The contractor is responsible for the proper removal and disposal of all ACM disturbed in the course of working on this project.

If all disturbed ACM materials will fit into one asbestos waste or glove bag, contractor's workers who are properly trained under OSHA Construction Standard Asbestos Regulations 29 CFR 1926.1101 may remove and dispose of the ACM using safe work practices.

If all disturbed ACM materials will not fit into one asbestos waste or glove bag, or if workers are not properly trained, the contractor shall hire a state certified asbestos abatement firm to remove and dispose of the disturbed ACM materials.

			v	
	Bid Cost:	Base	XQuantity	= Total Cost
Exterminate Termites			General R	Requirements
Exterminate for termites. Drill and patch foundation and paveme year guarantee with an optional yearly renewable warranty for the		sary. Exteri	minator must be lic	censed and provide a 1
	Bid Cost:		x	=
		Base	Quantity	Total Cost
Make Non-Original Windows Operable			Building \$	Systems
Remove plastic sheeting from windows in the living room, dining necessary to make windows operate smoothly and lock securely		nen. Inspe	ct windows and ma	ake minor repairs as
	Bid Cost:		х	=
	Bid Cost:	Base	XQuantity	=Total Cost
Install Storm Windows	Bid Cost:		Quantity	Total Cost
Install Storm Windows Install storm windows on all windows except at original front and			Quantity	
	d back porches.	Base	Quantity General R	Requirements
Install storm windows on all windows except at original front and	d back porches. Preservation O inimum. The dividence of the control of the cont	Base ffice and make ision of the es must no	Quantity General R ust meet the follow storm t be	Requirements
Install storm windows on all windows except at original front and Storm windows are subject to pre-approval by the State Historic The visual impact of adding storm windows must be kept to a m windows, if any, must align with the meeting rail of the historic windows.	d back porches. Preservation O inimum. The div vindow, the fram ich that of the wi	Base ffice and m rision of the es must no ndow sash	Quantity General R ust meet the follow storm t be	Requirements
Install storm windows on all windows except at original front and Storm windows are subject to pre-approval by the State Historic The visual impact of adding storm windows must be kept to a m windows, if any, must align with the meeting rail of the historic wexcessively bulky, and the color of the storm windows must mat	d back porches. Preservation O inimum. The divindow, the frame ich that of the with	ffice and maision of the es must no ndow sash your bid.	Quantity General R ust meet the follow storm t be	Requirements
Install storm windows on all windows except at original front and Storm windows are subject to pre-approval by the State Historic The visual impact of adding storm windows must be kept to a m windows, if any, must align with the meeting rail of the historic wexcessively bulky, and the color of the storm windows must mat Submit specifications and examples of the storm window you in	d back porches. Preservation O inimum. The divindow, the frame ich that of the with	ffice and m rision of the es must no ndow sash your bid. ion.	Quantity General R ust meet the follow storm t be	Requirements

Upgrade Electrical System

Buildings Systems

Upgrade the electrical system to comply with all requirements of the current NC Electrical Code. This includes but is not limited to:

*de-energize and remove all knob and tube wiring throughout the structure

*other existing wiring may be re-used provided it is in full compliance with the Electrical Code

*Replace electrical service with new 110/220 volt, 200 amp panel with main disconnect and 24 circuit panel board; meter socket; weather head; service cable; and ground rods and cable. Caulk exterior service penetrations. Label circuits legibly. Replacement of all sub-panels is included.

*Install GFCI breakers on all two wire receptacle circuits. Install GFCI/AFCI breakers on all two wire bedroom receptacle circuits. Label outlets per Code requirements.

*install new wiring, outlets, and devices as necessary to comply with the Electrical Code or to service existing equipment or to power items and equipment added to the structure by other items in this scope of work.

*scope includes installation of smoke and CO detectors as required by the Electrical Code

*scope includes GFCI devices at Code required locations.

*Replace receptacles, switches, and cover plates at all existing outlets that are incorporated into the upgraded electrical system. Remove devices from abandoned outlets and install blank cover plates.

*anything else required to produce a safe, fully functioning electrical system in full compliance with the current NC Electrical Code.

* scope includes repair of all ceiling, wall, and floor tear out.

	Bid Cost:	x		
		Base	Quantity	Total Cost
Light Fixture Replace			Interior	

Install ceiling mounted 2 bulb UL approved light fixtures with LED bulbs and covers in all rooms with existing ceiling mounted fixtures.

Bid Cost: X = Base Quantity Total Cost

Ceiling Fans with Light Kits Interior

Remove existing ceiling fans and replace with new 52" 3 speed flush mounted ceiling fans with a minimum three bulb UL approved light fixture with globes and LED bulbs.

New fans are to be Energy Star rated.

Bid Cost:		X=	.
	Base	Quantity	Total Cost

Install Light at Front steps Install a switched light at the front door. Installation includes all finished surfaces.	necessary wiri	ng. Run wiring	Exterior in wall cavity and r	epair disturbed
	Bid Cost:	x	=_	
		Base	Quantity	Total Cost
Install Light Fixture			Bathroom	
Install a switched, UL approved, wall mounted 3 or 4 bulb LED	light fixture with	shades and la	imps above the van	ity
Installation includes all necessary wiring per the NC Electrical C	Code.			
	Bid Cost:	x	=_	
		Base	Quantity	Total Cost
Bath Exhaust Fan			Bathroom	
Install a switched ceiling mounted Energy Star rated exhaust fa at 100 cfm.	n in the ceiling.	Fan shall be	quieter than 2 sones	s and shall move air
Proper installation of metal vent and roof or wall cap/damper as	sembly is inclu	ded.		
Installation of all necessary wiring for fan and switch is included	I. Switch shall t	oe flush mount	ed near the door.	
All materials and work shall comply with the Electrical and Med	hanical Codes.			
	Rid Coots	x	_	
	Bid Cost:	Base		Total Cost
Remove Existing Floor Insulation			General Requ	uirements
Remove existing floor insulation and dispose of properly.			•	
Note: Some insulation is moldy. Use safe work practices when	n handling.			
	Bid Cost:	x	=	
		Base	Quantity	Total Cost
Masonry Pier Replace			General Requ	uirements
Brace up floor system temporarily as necessary and remove the	ree damaged or	undermined p	iers.	
Dig down to sound soil at a sufficient depth to support the latera	al loads of the p	iers.		
Pour concrete footers and install new masonry piers with morta	red joints.			
Size footers and piers per the Building Code. County inspection	ns required.			

Bid Cost: ___

Base

Quantity

Total Cost

Gut and Rebuild Bathroom Bathroom

Tear out all fixtures and gut bathroom and adjoining closet to the framing.

Remove closet door from bedroom. Keep the bedroom side door casing. Frame in the opening and install drywall on the bedroom side of the wall. Prime and paint to match existing. Re-install the bedroom side door casing.

Remove wall framing between bathroom and closet to create one room.

Correct wall and ceiling framing as necessary to provide a sound and flat surface for the installation of drywall. Install a head wall to accommodate the shower.

Install black plastic over interior window sashes and frame in opening as necessary to support drywall or tile board.

Reframe floor system to provide a sound and flat floor surface. Install 3/4" plywood subfloor.

Insulate floor, wall, and ceiling cavities as required by Code.

Bid Cost: X = Base Quantity Total Cost

Replumb Supply Lines Building Systems

Remove all existing water supply lines. Install new PEX supply lines to code to service one 3-piece bath, kitchen sink and washing machine. Includes replacement of spigots at front and back of house. Repair any wall or ceiling tear out required to install system.

NOTE: INSULATION ON SOME PIPING IS ASSUMED TO BE AN ASBESTOS CONTAINING MATERIAL. REFER TO THE LINE ITEM FOR THE REMOVAL OF ASBESTOS CONTAINING MATERIALS.

Replumb Waste Lines & Vents

Building Systems

Remove all drain, waste and wet vent lines to code legal dump. Install schedule 40 PVC to service one 3-piece bath, kitchen sink, and washing machine from the roof vent pipe/pipes thru the foundation wall to include a main clean out outside of house and any interior clean outs required, installed to code. Repair any wall or ceiling tear out required to install system.

Bid Cost: _____ X___ = ____ Base Quantity Total Cost

Washer Box Kitchen

Install a flush mounted washer box with all plumbing supply and drain line connections.

Venting may be supplied by Stud-i-Vent or equal.

Scope includes installation of new hot and cold water supply lines within the wall cavity and connection to existing water lines under the house.

Scope includes installation of new drain line within the wall and under the house as far as necessary to comply with Plumbing Code requirements.

Plumbing inspection is required.

Installation includes wall repair and painting to blend with surrounding surface as close as possible.

	Bid Cost:	x		<u> </u>	
		Base	Quantity	Total Cost	
Canian Fasy Assess Chausan Baskana			Dothassa		

Senior Easy Access Shower Package

Bathroom

Install blocking for three grab bars at locations determined by rehab specialist and home owner.

Install a 36" x 60" fiberglass shower pan. Pan must be pre-approved by City rehab specialist.

Install cement tile backer board and a ceramic tile surround. Owner's choice of tile.

Install new drain and mixing valve with all associated plumbing lines. Mixing valve shall be located in the center of the long wall of the shower to be accessible from a seated position. Install a diverter valve with a handheld sprayer beside the mixing valve. Shower head shall be located as normal. Install grab bars at designated locations.

Install tempered glass sliding shower doors.

Provide an approved seat manufactured for use in showers.

All materials and work shall comply with the Construction Specifications and the Plumbing Code.

	Bid Cost:	X_	<u> </u>	
	Ва	se	Quantity	Total Cost
Drywall Entire Room			Bathroom	

Drywaii Entire Room

Install 1/2" moisture resistant drywall using screws.

Tape the joints, apply three coats of joint compound, and sand to a smooth paint ready surface.

Materials and workmanship shall comply with the Construction Specifications.

Bid Cost: _		X=	<u> </u>
	Base	Quantity	Total Cost

Paint Entire Room Bathroom Remove or cover hardware, fixtures, accessories, and other room contents that are not to be painted. Prime all surfaces and top coat with two coats of low semi-gloss VOC acrylic latex paint. Surfaces to be painted include all walls, ceiling, trim, and doors. Ceiling shall be painted the owner's choice of white or the selected wall color. Replace or uncover hardware, fixtures, accessories, and other room contents. Quantity **Total Cost Sheet Vinyl Flooring Bathroom** Install 1/4" underlayment, properly nailed and leveled. Install full glue down sheet vinyl flooring with a 25 year manufacturer's warranty. Vinyl must be approved by the Rehab Specialist at the pre-construction meeting. Provide owner with a minimum of three patterns from which to choose. Install baseboard as necessary to match the existing and install quarter round around the perimeter of the vinyl. Install appropriate transition strips where vinyl meets other flooring types. Quantity Vanity **Bathroom** Install a new 24" vanity cabinet complete with marble-lite top with preformed sink. Install single handle metal faucet with P- trap and drain lines to the wall, pop-up drain plug, supply lines, full port ball type shut-off valves & escutcheon plates. All materials and workmanship shall meet the requirements of the NC Plumbing Code and the Construction Specifications. Quantity **Total Cost** 17" Height Commode Replace Install a 17" height, 2 piece, close coupled, white, vitreous china commode with a maximum water usage per flush of 1.6 gallons. Include plastic or pressed wood white seat, supply pipe, shut-off valve, flap valve and wax seal.

Total Cost

Medicine Cabinet

		throom sink.			
All materials and work to comply with the Construction Standar	ds.				
Cabinet to be approved by home owner and rehab specialist be	efore installation				
	Bid Cost:		X	=	
		Base	Quantity	Total Cost	
Accessory Set - 3 Piece Chrome		Bathroom			
Install a chrome plated steel bathroom accessory set consisting	g of a 24" towel l	bar, hand to	wel ring, and toi	ilet paper holder.	
	Bid Cost:		x	=	
		Base	Quantity	Total Cost	
Attic Access			Genera	l Requirements	
Remove suspended ceiling in hall way. Frame a Code legal size wooden or plywood dam around the access hatch high enough		•		1/4 dasing. Install a	
Install 1/2" drywall on the hall ceiling and finish and sand to a p the ceiling. Prime and paint all new materials ceiling white.	aint ready condi		small bed mold	around the perimeter of	
· · · · · · · · · · · · · · · · · · ·	·			_=	
· · · · · · · · · · · · · · · · · · ·	·		x	= Total Cost	
the ceiling. Prime and paint all new materials ceiling white.	·		XQuantity	= Total Cost	
the ceiling. Prime and paint all new materials ceiling white. Floor Repair	Bid Cost:		XQuantity	= Total Cost	
the ceiling. Prime and paint all new materials ceiling white. Floor Repair Remove top layer of floor covering and its underlayment.	Bid Cost:	Base	XQuantity Kitcher	= Total Cost	
the ceiling. Prime and paint all new materials ceiling white. Floor Repair Remove top layer of floor covering and its underlayment. Cut back other layers of floor coverings at the washing machine.	Bid Cost: e as necessary. ace even with the	Base ne remainder	X Quantity Kitchen	Total Cost	
Floor Repair Remove top layer of floor covering and its underlayment. Cut back other layers of floor coverings at the washing machine Repair subfloor and floor framing to produce a sound level surf. NOTE: THE THIRD LAYER DOWN OF FLOOR COVERING IS	Bid Cost: e as necessary. ace even with the	Base ne remainder	X Quantity Kitchen	Total Cost	
Floor Repair Remove top layer of floor covering and its underlayment. Cut back other layers of floor coverings at the washing machine Repair subfloor and floor framing to produce a sound level surf. NOTE: THE THIRD LAYER DOWN OF FLOOR COVERING IS	Bid Cost: e as necessary. ace even with the SAN ASBESTO TERIALS.	Base ne remainder	Quantity Kitchen of the floor cov	Total Cost Total Cost Vering. L. REFER TO THE LINE	

Bathroom

Interlocking Vinyl Plank Flooring

Kitchen

Install 1/4" underlayment per the IVP manufacturer's instructions.

Install waterproof interlocking vinyl plank flooring.

Flooring shall have a minimum 25 year manufacturer's warranty and shall be installed strictly according to manufacturer's specifications.


Contractor is responsible for preparing sub floor as necessary to satisfy manufacturer's installation specifications.

Install suitable matching transition pieces where flooring meets other flooring materials.

Install painted or stained wood quarter-round at all perimeters to complete installation.

Provide home owner choice of three to five pattern selections from program approved manufacturers.

	Bid Cost:	x_	=_	
		Base	Quantity	Total Cost
Certification				
Contractor Name:			Total Cost:	
Signature:			Date:	



New Bathroom Layout

Not to scale

Incorporates
adjoining existing
closet. See scope
of work for details

LEAD ABATEMENT SCOPE OF WORK & INSTRUCTIONS TO BIDDERS

Address

422 Ridgeway Ave.

8/19/2020

Complete the following scope of work:
em# Feature Method

**	reature	ivietnod	Number	COST P COST
1	Windows B2 through B8	Scrape and paint all exposed exterior window components.		19
2	Side Bcrawlspace door and frame	Close and tightly secure inner door to frame. Remove protruding hardware on exterior door. Cover door assembly with Tyvek and screw a piece of pressure treated 1/2" plywood to the frame to cover the assembly completely		
3	Side Brear porch corner post	Scrape and paint visible parts of corner post		
4	Side Crake overhang	Cover exposed wood with Tyvek and replace missing vinyl soffit pieces to match existing as close as possible.		
5	Room 5Door D1 (to basement)white wood door, casings, header, jambs and stops. Also exposed brown wood siding in stair well.	Make door smooth and operable. Scrape and paint all components.		
6	Room 5	Complete specialized cleaning throughout the room (see LIRA for dust levels)		


Total Bid: \$		
The undersigned contractor agrees to perform the scope of work for the fee in accordance with applicable regulations and the project manual. Tundersigned also certifies that the work will be completed within	he	
Signature of authorized contractor representative	auys or unard.	
Contractor Submitting Bid: Address:		
Phone:		

ROY CONSULTING GROUP CORPORATION Providing integrated environmental and geotechnical solutions

422 Ridgeway Avenue

Charlotte, NC 28204

SIDE C



SIDE B

SIDE A

Legend

= Window

= Soil Sample Location

NOT TO SCALE

SIDE D